

**DATA SHEET/SPECS - Model 22010**
**12 Channel Audio Presence Monitor**


Data Check's 12 Channel Audio Presence Monitor compliments its Audio Speaker Monitor and its many video monitors. Occupying 1 RU, this economical product offers a total package of versatile monitoring features in minimal space.

**Features**

- ▶ Easy monitoring of 6 stereo or 12 mono signals in small 1 RU space
- ▶ 12 full range precision VU meters with international standards for ballistics and hysteresis
- ▶ Color LED 10 segment bar graph display (Green, Yellow, Red) with adjustable brightness
- ▶ Accepts wide range of input levels from -20 dB to +3 dB
- ▶ Isolated inputs enable chained applications without signal overload

**Benefits**

- ▶ Broad number of applications in minimal space
- ▶ Easy viewing of multiple audio-channel levels
- ▶ Eliminates extraneous signals from affecting audio signal
- ▶ Usable in applications with subdued lighting
- ▶ Individual level control for professional or commercial applications

**Specifications**

- |  |  |
|--|--|
| <ul style="list-style-type: none"> <li>▶ 19"W x 1.75"H x 5"D</li> <li>▶ 482.6mm (W) x 44.5mm (H) x 127mm (D)</li> <li>▶ Weight: 6 lbs.</li> <li>▶ Input Levels from <math>\infty</math> to +22 dB</li> <li>▶ Input impedance &lt;10K</li> <li>▶ Frequency range 20 Hz to 20KHz <math>\pm</math> 3 dB</li> <li>▶ Display range -30dB to +7 dB</li> <li>▶ Isolated RCA input connectors</li> </ul> | <ul style="list-style-type: none"> <li>▶ Rear panel sensitivity adjustment for each channel</li> <li>▶ 18 VAC operation (standard power jack) 1A</li> <li>▶ Wall Wart power supply</li> </ul> <p><b>Optional</b> (Specify at time of order)</p> <ul style="list-style-type: none"> <li>▶ Isolated BNC input Connectors</li> <li>▶ AES/EBU digital inputs</li> <li>▶ Balanced XLR Inputs</li> </ul> |
|--|--|