

## DATA SHEET - Model 26010 Six Pack

### 6 Channel Video Monitoring System



#### Six Pack Features & Benefits

- ▶ 6 LCD Color Display in 2RU
- ▶ Bright, Clear Exceptionally Sharp Picture
- ▶ Auto-Switchable Between NTSC & PAL
- ▶ Adjustable Vertical Tilt
- ▶ Rugged Durable Construction
- ▶ Blue Field/Color Kill Front Panel Control
- ▶ Individual Front Panel Controls
- ▶ Superior Energy Savings



**Adjustable  
Viewing  
Angle**

#### The Strength of Six Pack Monitoring

- ▶ Satellite & Telco Feeds
- ▶ Cable Head-In & Video Transmission
- ▶ Mobile/ENG News
- ▶ Fiber Optic & Broadband Lines
- ▶ Camera, Production & Graphics Use
- ▶ Post Production & Edit Bays
- ▶ Production & Events

#### Prominent Users of the Six Pack Include

- ▶ ABC News at the White House
- ▶ AOL/Time Warner
- ▶ Armed Forces Radio & TV Services
- ▶ Avaya
- ▶ Canadian Broadcast Network
- ▶ CBS Television City
- ▶ Cisco Systems
- ▶ ESPN
- ▶ Federal Aviation Authority
- ▶ G.E. Americom
- ▶ Industrial Light + Magic
- ▶ KOMO-TV
- ▶ Lucent Technologies
- ▶ NASA
- ▶ Pan Am Satellite
- ▶ Pan American Sports Network
- ▶ Pinnacle Systems
- ▶ SeaChange
- ▶ Sony
- ▶ Televisa
- ▶ Turner Broadcasting
- ▶ U.S. Navy
- ▶ Viacom
- ▶ The Walt Disney Company
- ▶ WBNS-TV
- ▶ The White House



**DATA  
CHECK**

**Brilliance** In Confidence Monitoring

## SPECS - Model 26010 Six Pack



### Model 26010 - 6 Channel Video Monitoring System Specifications

**General Description:**

- ▶ The rack contains six 2.5" LCD color displays on a panel tilting  $\pm 20$  degrees.

**Enclosure/Dimensions:**

- ▶ Standard 2 RU 19" Rack
- ▶ 19"W x 3.5"H x 12"D
- ▶ Cubic Inches: 798
- ▶ Weight: 12 lbs.

**Boxed Dimensions:**

- ▶ 22"W x 7"H x 16"D
- ▶ Cubic Inches: 2464
- ▶ Weight: 14 lbs.

**Interface:**

- ▶ Each channel position:
  - ▶ Two 75 Ohm BNC connectors
  - ▶ One 2-position impedance switch
  - ▶ 75 Ohm/10k Ohm selection)
  - ▶ Level: 1 V PP

**Power:**

- ▶ 115/230 VAC, 50/60 Hz;
- ▶ Optional  $12 \pm 1$  VDC @ 5 amps

**Standard:**

- ▶ Composite Video
- ▶ NTSC & PAL auto-switchable

**Features:**

- ▶ One red LED Tally indicator per channel
- ▶ Brightness, contrast, color and hue controls on front panel
- ▶ Blue field on/off and color kill on/off on front panel

**LCD/TFT Display** (6 per chassis):

- ▶ Active Area: 2.5" Diagonal
- ▶ Pixel Arrangement: 160 x 234, delta
- ▶ Pixel (RGB) Trio Pitch: 0.106 (H) mm x 0.157 (V) mm
- ▶ Brightness, typical,  $0^\circ$ : 300 cd/m<sub>2</sub>
- ▶ Contrast Ratio,  $0^\circ$ : 160:1
- ▶ Viewing Angle, contrast > 10:1:  $+55^\circ$ H;  $+15^\circ$ ,  $-35^\circ$ V
- ▶ Response Time, max (Tr/Tf): 30/50 ms
- ▶ Light Source (standard): CCFL
- ▶ Window (Display Area): 2.03" (H) x 1.48" (V)